

Speedy ! Facile !



4 roller Laminator A3 size

Multi-function High Quality Laminator

4 Rollers Memory Reverse Auto Auto up to 250mic. Function Heat Off Motor Off Function Function Roller reverse prevents film Jamming Laminates 250 mic. Stand-by Mode vitches off the heat automatically Various thickness Stores the previous Switches off the Motor and Cooling Fan automatically settings settings available pouches

BAUMGARTNER

<u>BÜROAUTOMATIK AG</u>

Preset

111111

Laminates up to 250 micron pouches. Equipped with 4 heating rollers. Equipped with useful functions for safety and comfort. Stand-by and Motor OFF Mode will automatically switch off the Heat and Motor after a period of inactivity, providing peace of mind for the operator and saving energy.





From business card size up to A3 (Max. Laminating width 330mm)



Lamipacker LPD3224 HOLLY is ideal for quality lamination. Paper jams can be prevented by using the roller reverse switch. The heat and the motor will switch off automatically for Safety and for Energy saving. The machine can laminate films up to 250 micron.

Features

- Internal heating system provides both Heat and Pressure at the same time to the material. It is an ideal system for high quality adhesion of Film and ensures stable lamination.
- To achieve a quality finish a 4 roller transport mechanism is built into this compact laminator.
- Temperature setting is easy: Just choose the right setting for your lamination.
- Reverse switch prevents film jams.
- Stand-by Mode: The heat will switch off automatically after being idle for 15 minutes.

Motor OFF Mode: The motor and the cooling fan will switch off after 45 minutes of entering Stand-by Mode.

Pre-Set Button: The appropriate temperature for the film thickness is already predetermined. The previous setting is restored. All these functions offer you an easy, quick handling.

Specifications

Model	Lamipacker HOLLY
ltem No.	LPD3224
Max.Laminating Width	330mm (A3)
Max.Laminating Thickness	0.8mm (including film thickness)
Laminating Speed	530mm/min. (50Hz) 636mm/min. (60Hz)
Laminatable Film Thicknesses	80 - 250 microns
Temperature Range	100 - 160°C
Warm-Up Time	Approx. 5 -10 min.
Heating Method	4 roller heating, transport mechanism/internal heating system
Power Source / Power Consumption	AC 220-240V (50/60Hz) / 840W
Dimensions / Weight (excl. Rear Tray)	592 (W) x 210 (D) x 123 (H)mm / 11.0kg
Attachments	Rear Tray, Instruction Manual
Remarkable Function	Memory Function / Reverse Function / Stand-by Mode / Motor Off Mode / Pre-set Function
Package Size / Weight	720(W)x310(D)x260(H)mm / 13.0kg

*Warm-up time depends on room temperature. *Specification may be modified without prior notice

Contact:

Benefits

- •Lamination provides the document with a durable and water resistant jacket which provides protection from Scratches, Stains and Moisture.
- Colour Prints are not only more durable but also Vivid and Alive as the process makes the surface Flat and Smooth.
- •Laminated objects, such as documents or printed materials, are completely sealed and protected from oxidization of ink, color fade-out or changing colors.
- Ousing Film in a variety of sizes, thicknesses and finishes the Lamination possibilities are extensive, plus for those applications where protection from harmful UV rays is important Fujipla UV Cut Pouches are essential.

Lamination Film

It is recommended to use our genuine FUJIPLA "CP-Leaf". Use of other films may cause trouble (e.g. jamming etc.)

⚠ Safety Warning

- Read the instruction manual thoroughly before operation to avoid danger and failure of the lamination.
- In the cases listed below, please stop operation, unplug and contact your FUJIPLA dealer immediately.
 - The power supply cord or plug gets unusually hot.
 - Strange smell or smoke comes out.
 - Water or foreign objects get inside the machine.
- •Warning and caution signs are omitted in the photographs run on this catalogue.
- •Specification and appearance of the product may change for improvement reasons without notice.
- Maintenance parts for maintenance service are available for a minimum of 5 years after cessation of the manufacture of product.

This catalogue is valid as of May 2011

ROAUTOMATIK AG Mettlenstrasse 6 8472 Seuzacl Telefon 052 223 00 11 Fax 052 222 36 97 info@bueroautomatik.ch